

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Resin-moulded semiconductor hybrid module and manufacturing method thereof

Patent Number: EP0936671

Publication

date: 1999-08-18

Inventor(s): KAMIMURA NORITAKA (JP); TAKAHASHI MASAOKI (JP); SAEKI JUNICHI (JP); TAMBA AKIHIRO (JP); YAMADA KAZUJI (JP); GOUDA MASAHIRO (JP); ISHII MAKOTO (JP); OGAWA TOSHIO (JP); SUZUKI KAZUHIRO (JP)

Applicant(s): HITACHI LTD (JP)

Requested

Patent: ☐ EP0936671

Application

Number: EP19990101733 19990211

Priority Number

(s): JP19980029491 19980212

IPC

Classification: H01L25/16; H01L23/433

EC


Classification: H01L25/16H, H01L23/433E

Equivalents:

☐ JP11233712, ☐ US6291880

Cited

Documents: EP0774782; US5699609; US5077595; JP8298299**Abstract**

A semiconductor device includes a main circuit part having a semiconductor device formed on an electrode plate (13) of a lead frame and a control circuit part having protective functions, which is integrally molded by a resin mold part (30) into an integral mold structure. 

Data supplied from the esp@cenet database - 12